

SPECIFICATIONS & MORE

HumaRoll

> System Specifications



Human

Diagnostics Worldwide

HumaRoll

Small Bench Top Tube Roller

System Overview

Cat.no.	15460 (100 - 240 VAC) 50/60Hz EU Plug (IEC-60320C13 connector)
Maximum speed	70 rpm
Amplitude	24 mm
Maximum capacity:	4 kg
Display	Scale
Number of rolls	6
Roll diameter	30 mm
Roll length	280 mm
Speed set range	0 – 70 rpm
Operation mode	Continuous operation
Acceleration rate	Fix acceleration rates
Braking rate	Fix breaking rates
Motor	DC motor

General

Physical dimension (WxDxH)	Instrument without any components:	26 x 47 x 12 cm
	Space required for routine use:	35 x 55 x 12 cm
	Packaging:	35 x 58 x 25 cm
	Weight:	Gross: 6 kg, net: 4.5 kg
Electrical requirements	110...240 VAC 60/50 Hz	
	Power consumption 25 W	
Environmental	Operating: temperature: 5 °C...40 °C, Humidity: max. relative humidity of 80% non condensing	

Standard Accessories

User Manual	Cat.no. 15460/1
PowerCable	Cat.no.
Spare Fuse	Cat.no.